

<i>SHORT CAPACITY IN GRAM</i>	30	60	100	150	200	250	500	750	1000
<i>DIAMETER INJECTION PLUNGER IN MM</i>	28	32	40	45	50	55	60	65	70
<i>STRCK OF INJECTION PLUNGER IN MM</i>	180	210	235	275	325	400	475	550	625
<i>MAX. MOULD HEIGHT</i>	150	150	215	225	250	260	280	330	380
<i>MOULD OPENING MM</i>	150	150	240	250	270	290	310	325	370
<i>MOULD CLOSING PRESSURE KG/CM</i>	110	110	120	120	130	150	150	160	160
<i>OIL CAPACITY LITERS</i>	60	60	100	110	120	135	150	170	180
<i>HEATING CAPACITY KW</i>	600	750	1000	1000	1500	1800	2000	2000	2500
<i>ELEC. MOTOR CAP.RPM 1440 HP</i>	2	2	3	3	5	5	7.5	7.5	10
<i>PUMP PRESSURE CAP KG/CM</i>	110	110	120	120	130	150	150	160	160
<i>LOCKING FORCE IN TONS</i>	25	25	35	35	40	45	50	60	70

SHORT WEIGHT CAPACITY START FROM 60 GM TO 45 K.G